



BRACKET KIT #14510
 INST ALLA TION INSTRUCTIONS
 1998-1999 Chevrolet CK Ext. Cab Pick Up

EXT CAB APPLICATIONS USE BOARDS PART #14080/16080

Hardware:


(8 x) 5/16"x 3/4" hex head bolts
 (16 x) #14 T ek screws
 (8 x) Main brackets
 (8x) Bracket clamps

(8x) 5/16" Carriage bolts
 (24 x) 5/16" flat washers
 (8 x) Body rail channels

(8 x) 5/16" x 2"Hex head bolts
 (24 x) 5/16" Nylock nuts
 (8 x) T wist brackets

Installation:

1. Locate placement of brackets as follows: Starting from the front wheel well measure back and mark the locations at 11", 29", 48", 68"
2. Pre-assemble hanger twist strap to brackets using 5/16"x3/4 hex head bolts, flat washers and nuts – do not tighten.
3. Lay the short end of the bracket onto the "L" body rail which is already on the truck. One rail extends from front to rear on both the driver and the passenger side of the truck. Position the rail channel with the longest side parallel to the inside of the "L" body rail. Install a 5/16 x 2" hex head bolt through the bracket, through the hole in the rail channel and place a flat washer and lock nut and hand tighten.
4. Rest the angle of the twist strap on the pinch weld, then using Tek screws attach into the side wall (2 screws, one through each hole in the twist strap). Repeat for remaining brackets.
5. Tighten the bolt securing the twist strap to the bracket. Repeat for remaining brackets.
6. Tighten the bolt at the short end of the bracket (this will lock the bracket, rail channel and "L" body rail together. Repeat for remaining brackets.
7. Install the bracket clamps for the board to the long end of each bracket using 5/16" carriage bolts, flat washers and lock nuts – leave loose. Repeat for remaining brackets.
8. Lay board on brackets in desired position. Turn bracket clamps in position over top of lips on board and tighten bolts.
9. Repeat for other side.



Warranty Information

Rampage products, Inc. warrants to the original purchaser of any top it manufactures, that the top will be free of defects in material or workmanship for a period of 1 year from date of purchase. Such obligations under this warranty shall be limited to the repair or replacement, at Rampage products discretion, of any assembly or parts which, upon examination by Rampage products, Inc. proves to be defective. All defective items must be returned with proof of purchase to Rampage products, Inc., freight prepaid. This warranty does not cover damage resulting from abuse, misuse, alteration, accident or damage in transit. Rampage products obligations under this warranty are limited to the aforementioned repair or replacement of warranty defects for which the return authorization has been received during the warranty period, and Rampage products, Inc. shall not be liable for any incidental or consequential damages arising from breach of this or any implied warranty.

Rampage Products 9225 Stellar Court Unit C, Corona, CA 92883-4919, U.S.A.
 Phone: (951) 277-4949 Fax: (951) 277-2295
 www.rampage products.com
 Made in China